ExperCAT: An Expert System for Analysis and Short-Term Prediction of Clear Air Turbulence

DTIC ELECYE JUNE : 1991

J. E. Peak

Computer Sciences Corporation Monterey, CA 93943-5006

Prepared for Atmospheric Directorate Monterey, CA 93943-5006




Approved for public release; distribution is unlimited. Naval Oceanographic and Atmospheric Research Laboratory, Stennis Space Center, Mississippi 39529–5004.

91-03551

ABSTRACT

An expert system approach to the analysis and short-term prediction of clear air turbulence (CAT) is presented. CAT is defined here as nonconvective turbulence occurring above 18,000 feet. ExperCAT is rule-based, contains a total of 65 rules and has extensive help and explanation features. The system's analysis procedure is to guide a human observer in identifying cloud signatures known to be associated with CAT. ExperCAT forecasts include an estimate of the turbulence intensity and a confidence factor. The user can optionally view the selections entered to arrive at the forecast. Three step-by-step example runs are provided.



ACKNOWLEDGMENTS

The author acknowledges the support of the Project Manager, the Naval Ocean Systems Center (NOSC), Code 54, Dr. J. H. Richter, Program Element 62435N, and the Program Sponsor, the Office of Naval Technology, Mr. J. Cauffman, for making this effort possible. Dr. Gary Ellrod of the Satellite Applications Laboratory at NOAA/NESDIS developed the original decision tree upon which this work is based.

TABLE OF CONTENTS

1.	Introduction		•	•	•	•	•	•	•	•	1
	ExperCAT Design										
3.	Example ExperCAT Runs		•	•	•	•	•	•		•	5
4.	Conclusions and Recommendations	s.	•	•	•	•	•	•	•	•	9
Refe	erences		•	•	•	•	•	•	•	•	11
aggA	endix										13

ExperCAT: An Expert System for Analysis and Short-Term Prediction of Clear Air Turbulence

1. Introduction

Clear air turbulence (CAT) is nonconvective turbulence that occurs at altitudes above 18,000 feet. The analysis and prediction of CAT is a difficult problem because it exists in relatively small areas and tends to change rapidly with time. The ability to analyze and forecast CAT requires a highly specialized, and therefore rare, expertise. Because it is a mesoscale phenomenon, CAT is difficult to diagnose by using relatively coarse (horizontal and temporal) resolution upper-air data measurements. For this reason, the focus of turbulence detection has shifted to the use of satellite imagery. Geostationary satellites are able to provide enough temporal and spatial resolution to detect CAT-producing conditions, assuming that such conditions can be related to cloud signatures seen on the image.

In a limited sense, diagnosis of turbulence based on cloud patterns is accomplished by the Satellite Image Analysis Meteorological Expert System (SIAMES) (Peak, 1989). SIAMES was developed using the expertise contained in the Navy Tactical Applications Guides (e.g., Fett et al., 1984). Turbulence is only one of many atmospheric parameters diagnosed during a SIAMES consultation session.

One of the foremost researchers of the relationship between CAT and cloud signatures is Dr. Gary Ellrod of the Satellite Applications Laboratory at NOAA/NESDIS. His latest report (Ellrod, 1989) contains a decision tree based on subjective techniques developed over the past ten years at the Satellite Applications Laboratory. The availability of this clear and concise

presentation of his extensive CAT expertise has led NOARL to propose an expert system for analysis and short-term prediction of CAT. The Ellrod decision tree was to provide the bulk of the expertise for the prototype system, and additional information from sources such as the NTAGs and a U.S. Air Force technical report were to be used to expand the prototype. For more information on expert systems, the reader is referred to the background presented in Peak and Tag (1989).

In this report, the development of this expert system, called "ExperCAT," will be detailed. In the next section, the ExperCAT design will be presented. In the following section, some example runs of the system will be presented. Finally, the ExperCAT development will be summarized and suggestions for future improvements and program verification will be presented.

2. ExperCAT Design

The requirement for ExperCAT is to analyze and forecast, in the short-range, atmospheric turbulence not associated with convection. The system is also required to use satellite imagery as the primary source of information on which to base its analyses. Because the available expertise that meets these requirements applies to high-level (>18,000 feet) turbulence, the system applies only to that region.

Because the frame-based SIAMES expert system (Peak, 1989) was the genesis for turbulence forecasting at NOARL, it was first thought that ExperCAT would also be implemented using frames.

SIAMES, however, involves a general analysis of all cloud features that are seen on a satellite image. Such a task is condu-

cive to the use of frame structures that embody the various aspects of the complete image analysis. ExperCAT has the more specific goal of isolating turbulence-related cloud signatures. The lines of reasoning and types of features to look for are more specific, so that rules were selected rather than frames.

The Ellrod decision tree was studied in great detail. The existing SIAMES turbulence information was examined to ensure that the decision tree included those situations as well. For the prototype, the goal-oriented approach of the Ellrod decision tree information made for a natural conversion to a backward-chaining inference system.

Based on these initial design decisions, the information from the decision tree was converted to rule form. The resulting prototype rule base contained 59 rules. An initial evaluation of the system was made by NOARL researchers, resulting in suggested improvements to the prototype. It is the improved version, ExperCAT 1.0, that is presented in this report.

For version 1.0, the rule base was expanded slightly to a total of 65 rules. An extensive explanation feature was also added. The goal is to help the user to understand the physical reasoning used to make the analysis/forecast. An added advantage is that the reasoning behind the decisions used might help the user to understand why confidence factors are low or high in given situations.

The main source of expertise for this hypertext-based explanation feature was the Ellrod decision tree manuscript (Ellrod, 1989) and an earlier, more detailed CAT paper (Ellrod, 1985).

Additional expertise came from the NTAG series (e.g., Fett et al., 1984) and from a U. S. Air Force technical report on CAT forecasting (Lee et al., 1979). The form of the ExperCAT help feature differs significantly from that in An Expert system for Shipboard Obscuration Prediction (AESOP) (Peak and Tag, 1989). In AESOP, the explanation mode invokes a comprehensive traverse of a hypertext network associated with the rules that contributed to the forecast. The reason that this form of explanation works so well in revealing the AESOP lines of reasoning is that the AESOP rules embody a cause-and-effect process. In ExperCAT, however, the CAT analysis is a progressive search for cloud signatures known to be associated with CAT. Thus, the sequence of questions does not itself reveal a physical process. Rather, each question, and the possible answers for it, progressively define a CAT likelihood. Therefore, the ExperCAT explanation feature was tailored to reveal the reasoning behind each individual question more than the sequence of questions. In ExperCAT, "Why do you ask?" and "Why are these selections important?" are the pertinent questions the user needs to ask the system.

The expert system begins with an analysis of the synoptic-scale, upper-level flow pattern. Each progressive rule narrows the evaluation of the situation with respect to the likelihood of CAT. When the system has enough information to make a judgment, the CAT analysis is presented along with a confidence factor. The turbulence categories are "Strong," "Moderate," "Light" and "No significant CAT." These intensities are from subjective turbulence reports of large commercial and military aircraft.

The confidence factors are from those included in the decision tree and are based on Ellrod's research efforts. In the next section, the function of ExperCAT 1.0 will be revealed through some example runs.

3. Example ExperCAT Runs

To demonstrate the way that ExperCAT functions, three stepby-step example runs are now discussed. These runs, for hypothetical image examples, are presented using actual ExperCAT screen displays in the Appendix.

ExperCAT begins with an introductory title screen and a text screen that explains how to select the menu items and help features (not shown). As in AESOP and SIAMES, the user moves a highlighted bar to the desired menu choice using the arrow keys and presses the carriage return to make the selection. Alternately, the first letter of the desired choice can be entered. The highlighted bar is delineated by color on the computer screen and does not appear on the figures in the Appendix. To assist the reader, an arrow is included on these figures to indicate which item is being selected. In an actual run, of course, these arrows would not appear.

To access hypertext help information about the questions being asked, the user can press the Fl key. For help about each potential selection for a given question, the user can move the highlighted bar to the desired choice and press F2.

The next screen that appears (SCREEN 1) includes the toplevel decision whether to make a forecast or exit the system. Since we have just started, we enter the former. This action is denoted on SCREEN 1 by an arrow pointing to the selection and an action in parentheses -- in this case, the carriage return, or (cr) for brevity.

The system's response is to display SCREEN 2. Here, Exper-CAT attempts to define the upper-atmospheric synoptic flow pattern. In SCREEN 2, we have the user choosing the help facility for a further explanation of the question by pressing Fl. A pop-up window containing the explanatory text appears at the bottom of the screen. Now suppose the user wants to know more about the three choices. He moves the highlighted bar to the first choice and presses F2 (SCREEN 3). ExperCAT responds by displaying another window of text. Notice that the explanation includes help in defining what is meant by "Straight or slightly curved flow," why this type of flow is important in relation to turbulence, and what possible exceptions to this rule might come into play. For completeness, we include the help information for the second choice (SCREEN 4) and the particularly long help screen text for choice 3 (SCREEN 5).

Assuming the user ultimately entered the first choice in SCREEN 5, ExperCAT continues the analysis (SCREEN 6). Again, we show the user asking for more information concerning the question about cirrus signatures (SCREEN 6) and then for help about the first choice (SCREEN 7). After looking at the help information for the second choice, we assume that the user chooses the first response, namely that transverse bands are present (SCREEN 8).

The next ExperCAT screen asks for a description of the curvature of the cold-air side of the cirrus SCREEN 9). The

user here asks for an explanation of the first choice, and then makes that choice. Notice that the help feature here includes information about where the turbulence is expected to occur (SCREEN 9). The analysis continues with questions about the wavelength of the curved cirrus cloud segment (SCREEN 10) and the shape of the transverse bands (SCREENS 11 and 12).

Finally, ExperCAT has narrowed the decision down and makes an analysis/forecast (SCREEN 13). As pointed out in the ExperCAT introductory screen (not shown), the CAT intensity here is that expected for large aircraft. If the user wishes a review of the selections he has made to arrive at this forecast, he can press F1 and the expert system's facts will be listed (SCREEN 14). In its present version, ExperCAT does not allow the user to change individual responses and then rerun the analysis as does AESOP (Peak and Tag, 1989). The reason for this design choice stems from the differences between the two rule base domains. AESOP performs an exhaustive analysis of potential visibility obscurations based on a fixed set of input parameters. ExperCAT, however, only asks for the information pertinent to its current line of reasoning. Thus, changing one answer usually causes all of the subsequent questions no longer to apply, and the user would have to reenter an entire, new sequence of answers anyway. For this reason, a modification feature was deemed unnecessary; the user must invoke a completely new run of ExperCAT to determine the effects of different input data. On the other hand, such a modification feature is certainly possible, and could be included if NOARL considers it necessary.

The second example run begins with the end of the previous one. When the forecast screen (SCREEN 13) is displayed, the user simply enters the carriage return to arrive again at the top-level decision screen (SCREEN 15). In this example, we choose the second type of synoptic flow -- sharply curved (SCREEN 16). Of the two types of sharply-curved flow, the user indicates that it is a trough (SCREEN 17). In SCREEN 18 the system looks for signatures that support turbulence when they occur in conjunction with a trough. The help text in SCREEN 18 elaborates on the physical connection between darkening in the water vapor channel and turbulence-production.

When the user affirms that water-vapor darkening is present, ExperCAT makes a forecast. Note that this time the forecast is accompanied by clarifying text concerning the location of the turbulence, help in establishing a confidence level, and what to look for in determining the dissipation of the turbulence (SCREEN 19).

For the third example run, we omit the top-level decision screen and proceed to the synoptic flow pattern question (SCREEN 20). This time, the last choice (hyperbolic flow) is selected. There are three possible cloud patterns associated with deformation zones (SCREEN 21). Here the user invokes the help feature (F2) to get an explanation of "delta-shaped cirrus," but then chooses the "comma cloud" selection. Because the different regions of a comma cloud have different turbulence-producing conditions, the question in SCREEN 22 narrows down the search for turbulence signatures. Further narrowing of the search is accom-

plished by the three types of synoptic situations to choose from in SCREEN 23. A further description of the comma itself occurs in SCREEN 24. Here, the help feature assists in explaining what is meant by "sheared comma." In future versions, a pictorial depiction of this, and other potentially ambiguous questions would be desirable.

The last information needed before the forecast is the sharpness of the cloud edge (SCREEN 25). Again, the help feature reveals the physical reason that this signature is important. The display of the forecast screen (SCREEN 26) ends this last example run.

4. Conclusions and Recommendations

In this paper, an expert system approach for analysis and short-term forecasting of clear air turbulence has been presented. The major source of expertise for the expert system rule base is the research of Dr. Gary Ellrod of NOAA/NESDIS.

The system described in this paper, named "ExperCAT," is version 1.0, having progressed through the design, prototype, and prototype revision stages of development. ExperCAT is rule-based, uses backward-chaining inference, and has a hypertext-based explanation/help feature. The system function is demonstrated through three example runs.

At this point, ExperCAT has not been verified using actual data because of the unavailability of CAT reports at NOARL. It is recommended that the system be verified to ensure its usability and correctness. One possible method would be to acquire a set of satellite images and CAT reports for historical cases.

Another possibility would be to use atmospher c profiler information in conjunction with real-time imagery. The author understands that such a profiler, soon to be located at Fort Ord, would be able to detect high-level CAT.

It would be desirable for the system to include diagrams or figures to assist in describing the various selections the user needs to choose between. In discussions with Buck Sampson of NOARL, the author has determined that the "PC-Paint" software in conjunction with a scanner might be used. It is recommended that this possibility be pursued. If NOARL considers it necessary, a modification/rerun feature could also be included.

The next logical step in ExperCAT development is to elicit an expert evaluation from the author of the main source of expertise used in developing the system, to ensure that the transition to an expert system has not led to the garbling or omission of key information. It is planned to send the latest version to Dr. Ellrod in hopes of obtaining his comments.

REFERENCES

- Ellrod, G.P., 1985: Detection of high level turbulence using satellite imagery and upper air data. NOAA technical memorandum NESDIS 10, Washington, DC 20233. 30 pp.
- , 1989: A decision tree approach to clear air turbulence analysis using satellite and upper air data. NOAA technical memorandum NESDIS 23, Washington, DC 20233. 30 pp.
- Fett, R.W., W.A. Bohan and J. Rosenthal, 1984: Navy Tactical Applications Guide, Vol. 4, Eastern North Pacific Weather Analysis and Forecast Applications; Naval Environmental Prediction Research Facility* technical report TR 83-01. 180 pp.
- Lee, D.R., R.B. Stull and W.S. Irvine, 1979: Clear Air Turbulence Forecasting Techniques. U.S. Air Force Global Weather Central technical note 79/001, AFGWC/TS, Offutt AFB, NE 68113. 68 pp.
- Peak, J.E., 1989: Initial expert evaluation and resultant modifications to the satellite image analysis meteorological expert system (SIAMES) prototype. Naval Oceanographic and Atmospheric Research Laboratory, Atmospheric Directorate, Monterey, CA 93943-5006. 12 pp plus appendices. (unpublished internal report)
- Peak, J. E. and P.M. Tag, 1989: An expert system approach for prediction of maritime visibility obscuration. Mon. Wea. Rev., 117, 2641-2653.

^{*}Now the Naval Oceanographic and Atmospheric Research Laboratory, Atmospheric Directorate, Monterey, CA 93943-5006.

APPENDIX EXAMPLE EXPERCAT RUNS

	E X P E R C A T Version 1.0 4/10/90
	Which would you like to do? Make a clear air turbulence forecast (cr) Exit from EXPERCAT
SCKE	EN 2: E X P E R C A T Version 1.0 4/10/90
	Which describes the upper synoptic flow pattern? (F1 Straight or slightly curved flow Sharply curved (ridge or trough) Hyperbolic (deformation zones)
	EXPERCAT HELP
patterns conduciv region o	thecking the synoptic pattern because, in general, upper flow is with shorter wavelengths and more curvature are more be to extensive turbulence. This question applies to the of interest in the next few hours, and the answer can be need from animated satellite imagery, upper wind charts, and/or
forecast	

SCREEN 3:

E X P E R C A T Version 1.0 -- 4/10/90

Which describes the upper synoptic flow pattern?— Straight or slightly curved flow ← (F2) Sharply curved (ridge or trough) Hyperbolic (deformation zones)

_EXPERCAT HELP__

This flow pattern includes broad, smooth upper lows, ridges or troughs and confluent jets. In general, turbulence is less likely to be associated with straight flow than with sharply-curved flow. The exception to this rule is when there are local areas of strong vertical shears generated by jet streaks.

SCREEN 4:

___E X P E R C A T Version 1.0 -- 4/10/90_

__EXPERCAT HELP_

In general, turbulence is more likely with curving jet stream segments, mainly in conjunction with sharp troughs and ridges.

SCREEN 5:

E X P E R C A T Version 1.0 -- 4/10/90

Which describes the upper synoptic flow pattern?—
Straight or slightly curved flow ← (cr)
Sharply curved (ridge or trough)
Hyperbolic (deformation zones) ← (F2)

EXPERCAT HELP-

A deformation zone is a region of hyperbolic flow where air parcels undergo stretching along one axis and contraction in the orthogonal direction. They are the most common large-scale turbulence signature. In both visual and IR imagery, deformation zones are often marked by the location of significant cloud boundaries. If the water vapor channel is available, deformation zones can usually be identified by moisture boundaries on that image. Turbulence occurs within 2-3 degrees latitude (330 km) of the deformation boundary, both in clear air and in cirrus clouds. When the winds intersect the isotherms at a large enough angle, deformation zones are frontogenetic in nature. It is these upper-level fronts that produce the high-level turbulence.

SCREEN 6:

E X P E R C A T Version 1.0 -- 4/10/90-

_____Do you see either of these cirrus signatures? ______(F1: Transverse bands (IR & VIS) or billows (VIS) Ragged poleward cirrus edge near jet with dense cirrus patches Neither cirrus signature

EXPERCAT HELP-

These cirrus signatures are important because they indicate atmospheric wind shear. In relatively straight flow, turbulence is caused by strong vertical shears. The presence of both speed and directional shear often results in wave cloud features. Strong speed shear can cause the poleward cirrus edge to become ragged or scalloped in appearance.

SCREEN 7:

EXPERCAT Version 1.0 -- 4/10/90---

EXPERCAT HELP

Speed and directional shear conditions often result in wave cloud features oriented transverse to the upper flow. Transverse bands are more irregular than billows, and are more likely to be observed in lower resolution IR images such as those from GOES. The presence of cirrus billows may indicate strong shear (Kelvin-Heimhoutz) instability. The longer the wavelength of the billows, the better the chance of significant turbulence.

SCREEN 8:

___E X P E R C A T Version 1.0 -- 4/10/90_

Transverse bands (IR & VIS) or billows (VIS)

Ragged poleward cirrus edge near jet with dense cirrus patches (F2)

Neither cirrus signature

__EXPERCAT HELP_

The ragged edge occurs with speed shear caused by ageostrophic accelerations near a jet streak. When turbulence occurs, wind speeds in the jet are usually 80 kt or greater.

SCREEN 9:

__E X P E R C A T Version 1.0 -- 4/10/90_

Describe the cold-air side of the cirrus—Anticyclonic curvature (F2,cr)
Straight or cyclonic curvature

EXPERCAT HELP-

Sharp, anticyclonically-curved bulges along the jet stream cirrus relate to jet streaks. The maximum winds are located near the crest of the cirrus bulge. When turbulence occurs, wind speeds in the jet are usually 80 kt or greater. The turbulence usually occurs from the crest of the bulge downwind for several hundred kilometers. This is the exit region of the jet where the air parcels decelerate rapidly.

SCREEN 10:

__E X P E R C A T Version 1.0 -- 4/10/30___

—How long is the wavelength of the curved segment?—— <=500 nm (e.g., 8-9 degrees of latitude) >500 nm (e.g., 8-9 degrees of latitude) ← (F2, cr)

EXPERCAT HELP-

Less curvature is less indicative of turbulence.

	FN		
		1 1	

___E X P E R C A T Version 1.0 -- 4/10/90____

Which best describes the cloud bands? (F1)
Wide, thick and carrot-shaped
Not wide, thick and carrot-shaped

EXPERCAT HELP

The shape of the cloud bands is important because it indicates the degree of turbulence. Wide, thick bands are those easily distinguished in low resolution IR images.

SCREEN 12:

E X P E R C A T Version 1.0 -- 4/10/90

— Which best describes the cloud bands?—— Wide, thick and carrot-shaped ◀ (F2,cr) Not wide, thick and carrot-shaped

EXPERCAT HELP

In general, the wider, thicker transverse bands are more likely to contain severe turbulence, possibly due to the added presence of thermal instability. In these situations, the bands often have a carrot-shaped appearance similar to that of Cb anvils.

SCREEN 13:

Clear Air Tu	urbulence: Moderate or Greater	
	Confidence: 70%	
•		

SCREEN 14:

EXPERCAT FORECAST (F1)

Clear Air Turbulence: Moderate or Greater

Confidence: 70%

EXPERCAT FACTS

Synoptic flow pattern is: Straight or slightly curved flow Cirrus signature is: Transverse bands (IR & VIS) or billows (VIS) Cold-air side of cirrus is: Anticyclonic curvature Curved segment wavelength is: >500 nm (e.g., 8-9 degrees of latitude) Cloud bands character is: Wide, thick and carrot-shaped

SCREEN 15:

SCREEN 16:

Which describes the upper synoptic flow pattern?

Straight or slightly curved flow
Sharply curved (ridge or trough)

Hyperbolic (deformation zones)

SCREEN 17:

Which type of sharply curved flow?

Ridge (on south side of jet)
Trough (preferably with strong upstream jet)

EXPERCAT HELP

It is also preferable that the trough have a north-south or northeast-southwest tilt.

SCREEN 18:

SCREEN 19:

___EXPERCAT Version 1.0 -- 4/10/90_____

EXPERCAT FORECAST

Clear Air Turbulence: Moderate or Greater

Confidence: 80%

The CAT is normally in the region of the most rapid water vapor darkening. If the darkening has persisted for at least 3 hours, there is higher confidence that turbulence is present. When the darkening ceases, turbulence diminishes.

SCREEN 20:

EXPERCAT Version 1.0 -- 4/10/90___

Which describes the upper synoptic flow pattern?—Straight or slightly curved flow Sharply curved (ridge or trough)
Hyperbolic (deformation zones)

SCREEN 21:

__E X P E R C A T Version 1.0 -- 4/10/90__

— Which cloud feature is present? Comma cloud ← (cr) Delta-shaped cirrus(IR/VIS, W-NW flow) ← (F2 Little or no cloudiness

-EXPERCAT HELP-

These features occur in west or northwest flow and usually are not associated with developing surface lows. They also have a different appearance in the imagery since the cirrus often forms in elongated bands transverse to the flow, probably due to the presence of gravity waves. Such cirrus can appear as a triangular-shaped area known as a delta region. The appearance of these features varies considerably, depending on the availability of moisture. Turbulence occurs within 2 to 3 degrees latitude (180 nm) of the leading edge of the clouds.

SCREEN 22:

__E X P E R C A T Version 1.0 -- 4/10/90_

Where is the forecast location with respect to the comma cloud?— Near the poleward edge of the comma head ← (F2,cr) In the dry slot Near the comma tail

EXPERCAT HELP.

The most significant turbulence with a comma cloud deformation zone occurs in conjunction with a developing cyclone. Each of these three locations has a different set of considerations in analyzing turbulence.

SCREEN 23:

Describe the synoptic situation

Deepening or steady-state upper-level low center (cr)
Upper-level low opening into trough or filling
Upper-level vorticity maximum with no closed low

SCREEN 24:

Which type of comma system is present?

Full comma ← (cr)

Sheared comma (the jet crosses over the cloud head)

EXPERCAT HELP.

___E X P E R C A T Version 1.0 -- 4/10/90_

During the comma development, the jet will sometimes continue to push through the comma cloud and cross over the ridge line. When this happens, the jet location will be marked by a sharp boundary between higher cirrus on the anticyclonic side and the lower-layer clouds forming the comma head.

SCREEN 25:

	f these conditions conditions
A share cl	EXPERCAT HELP————————————————————————————————————
	th indicators of turbulence.
SCREEN 2	s.
	EXPERCAT Version 1.0 4/10/90
	EXPERCAT FORECAST
	EAT ENGHT TOREGOST
	Class Air Turbulancas Madarata or Grantar
	Clear Air Turbulence: Moderate or Greater
	Clear Air Turbulence: Moderate or Greater Confidence: 70%

DISTRIBUTION LIST

SPAWARSYSCOM ATTN: PMW-141

WASHINGTON, DC 20363-5100

NOARL

ATTN: CODE 125L (10) JCSSC, MS 39529-5004

NOARL

ATTN: CODE 125P JCSSC, MS 39529-5004

NOARL

ATTN: CODE 300 JCSSC, MS 39529-5004 COMNAVOCEANCOM

ATTN OPERATIONS OFFICER JCSSC, MS 39529-5000

NAVAL OCEANOGRAPHIC OFFICE

ATTN: OPERATIONS OFFICER JCSSC, MS 39522-5001

NOARL LIAISON OFFICER ATTN: FARQUHAR BROOKE

2211 JEFFERSON DAVIS HWY ARLINGTON, VA 22202-50.3

OFFICE OF NAVAL TECHNOLOGY ATTN: DR. P. SELWYN, CODE 20

800 N. QUINCY ST. ARLINGTON, VA 22217-5000

OFFICE OF NAVAL TECHNOLOGY DR. M. BRISCOE, CODE 228 800 N. QUINCY ST.

ARLINGTON, VA 22217-5000

OFFICE OF NAVAL RESEARCH

ATTN: CODE 12 800 N. QUINCY ST. ARLINGTON, VA 22217-5000 COMNAVAIRSYSCOM ATTN: OPERATIONS

WASHINGTON, DC 20361-0001

PENNSYLVANIA STATE UNIV.

ATTN: APPLIED RSCH LABORATORY

P.O. BOX 30

STATE COLLEGE, PA 16801

COMMANDER IN CHIEF U.S. ATLANTIC FLEET

ATTN: NSAP SCIENCE ADVISOR NORFOLK, VA 23511-6001

COMMANDER IN CHIEF U.S. NAVAL FORCES, EUROPE

ATTN: METEOROLOGICAL OFFICER

FPO NEW YORK 09510

COMMANDER SECOND FLEET ATTN: METEOROLOGICAL OFFICER

FPO NEW YORK 09501-6000

COMSECONDFLT

ATTN: NSAP SCIENCE ADVISOR FPO NEW YORK 09501-6000

COMTHIRDFLT

ATTN: FLT METEOROLOGIST FPO SAN FRANCISCO 96601-6001 COMSEVENTHELT

ATTN: FLT METEOROLOGIST FPO SAN FRANCISCO 96601-6003

COMTHIRDFLT

ATTN: NSAP SCIENCE ADVISOR

PEARL HARBOR, HI 96860-7500

COMSEVENTHFLT

ATTN: NSAP SCIENCE ADVISOR

BOX 167

FPO SEATTLE 98762

COMSIXTHFLT

ATTN: FLT METEOROLOGIST FPO NEW YORK 09501-6002

COMSIXTHFLT/COMFAIRMED

ATTN: NSAP SCIENCE ADVISOR FPO NEW YORK 09501-6002

COMMANDER, MID EAST FORCE

ATTN: MET OFFICER

FPO NEW YORK 09501-6008

COMNAVAIRFORLANT

ATTN: HETEORO. OFFICER

NORFOLK, VA 23511-5188

COMMANDER NAVAL AIR FORCE U.S. ATLANTIC FLEET ATTN: NSAP SCIENCE ADVISOR NORFOLK, VA 23511-5188 COMMANDING OFFICER
USS AMERICA (CV-66)
ATTN: MET. OFFICER, OA DIV.
FPO NEW YORK 09531-2790

COMMANDING OFFICER
USS D. EISENHOWER (CVN-69)
ATTN: MET. OFFICER, OA DIV.
FPO NEW YORK 09532-2830

COMMANDING OFFICER
USS FORRESTAL (CV-59)
ATTN: HET. OFFICER, OA DIV.
FPO MIAMI 34080-2730

COMMANDING OFFICER
USS INDEPENDENCE (CV-62)
ATTN: MET. OFFICER, OA DIV.
FPO SEATTLE 96618-2760

COMMANDING OFFICER
USS J. F. KENNEDY (CV-67)
ATTN: MET. OFFICER, OA DIV.
FPO NEW YORK 09538-2800

COMMANDING OFFICER
USS NIMITZ (CVN-68)
ATTN: MET. OFFICER, OA DIV.
FPO SEATTLE 98780-2820

COMMANDING OFFICER
USS SARATOGA (CV-60)
ATTN: MET. OFFICER, OA DIV
FPO MIAMI 34078-2740

COMMANDING OFFICER
USS T. ROOSEVELT (CVN-71)
ATTN: MET. OFFICER, OA DIV.
FPO NEW YORK 09559-2871

COMMANDING OFFICER
USS A. LINCOLN (CVN-72)
ATTN: MET. OFFICER
FPO NEW YORK 09580-2872

COMMANDING OFFICER
USS CONSTELLATION (CV-64)
ATTN: MET. OFFICER, OA DIV
FPO NEW YORK 09558-2780

COMMANDING OFFICER
USS ENTERPRISE (CVN-65)
ATTN: MET. OFFICER, OA DIV.
FPO NEW YORK 09543-2810

COMMANDING OFFICER
USS KITTY HAWK (CV-63)
ATTN: MET. OFFICER, OA DIV.
FPO NEW YORK 09535-2770

COMMANDING OFFICER
USS MIDWAY (CV-41)
ATTN: MET. OFFICER, OA DIV.
FPO SAN FRANCISCO 96631-2710

COMMANDING OFFICER
USS RANGER (CV-61)
ATTN: MET. OFFICER, OA DIV.
FPO SAN FRANCISCO 96633-2750

COMMANDING OFFICER
USS CARL VINSON (CVN-70)
TTN: MET. OFFICER, OA DIV.
FPO SAN FRANCISCO 96629-2840

NAVOCEANCOMDET ATTN: METEOROLOGIST AFGWC OFFUTT AFB, NE 68113 NAVAL POSTGRADUATE SCHOOL ATTN: CODE MR MONTEREY, CA 93943-5000

NAVAL POSTGRADUATE SCHOOL ATTN: 0142 MONTEREY, CA 93943-5002 NAVAIRSYSCOM ATTN: AIR-723D WASHINGTON, DC 20361-0001 NAVAIRSYSCOM ATTN: CODE 526W WASHINGTON, DC 20361-0001

SPAWARSYSCOM ATTN: CODE 312 NAT. CTR. #1 WASHINGTON, DC 20363-5100

SPAWARSYSCOM ATTN: CODE PHW-141 NAT. CTR. #1 WASHINGTON, DC 20363-5100 NAVOCEANSYSCEN ATTN: J. RICHTER, CODE 54 SAN DIEGO, CA 92152-5000 PACHISTESTCEN ATTN: GEOPHYSICS OFFICER PT. MUGU, CA 93042 9HQ SAC/DOWA ATTN: MET. OFFICER OFFUTT AFB, NE 68113 AFGWC/DAPL ATTN: TECH. LIBRARY OFFUTT AFB, NE 68113

3 WW/DN ATTN: MET. OFFICER OFFUTT AFB, NE 68113 AFGL/LY ATTN: MET. OFFICER HANSCOM AFB, MA 01731 SWW/DN ATTN: MET. OFFICER LANGLEY AFB, VA 23665

COMMANDER/DIRECTOR ASL, WHITE SANDS ATTN: SLCAS-AE WSMR, NM 88002-5501 DIRECTOR, NMC ATTN: FORECAST SERVICES NWS, NOAA WWB W32, RM 204 WASHINGTON, DC 20233 DIRECTOR
NATIONAL EARTH SAT. SERV/SEL
ATTN: FB-4, S321B
SUITLAND, HD 20233

FEDERAL COORD. FOR METEORO. SERVS. & SUP. RSCH. (OFCM) 11426 ROCKVILLE PIKE ATTN: FORECAST SERVICES ROCKVILLE, MD 20852 NATIONAL WEATHER SERVICE ATTN: FORECAST SERVICES 5200 AUTH ROAD CAMP SPRINGS, MD 20023 NATIONAL SEVERE STORMS LAB ATTN: FORECAST SERVICES 1313 HALLEY CIRCLE NORMAN, OK 73069

NWS FORECAST OFFICE ATTN: FORECAST SERVICES 660 PRICE AVE. REDWOOD CITY, CA 94063 CHIEF, NESS ATTN: MESOSCALE APPL. BRANCH 1225 W. DAYTON MADISON, WI 53562 DIRECTOR, TECH. DEVELOP. LAB. ATTN: FORECAST SERVICES GRAMAX BLDG. 8060 13TH ST. SILVER SPRING, MD 20910

DIRECTOR, NWS ATTN: FORECAST SERVICES GRAMAX BLDG. 8060 13TH ST. SILVER SPRING, MD 20910 NCAR ATTN: ACQUISITIONS P.O. BOX 3000 BOULDER, CO 80307 NATIONAL SCIENCE FOUNDATION ATTN: ATHOS. SCIENCES DIV. 1800 G STREET, NW WASHINGTON, DC 20550

DR. MARVIN DICKERSON L-262, LLNL P.O BOX 808 LIVERMORE, CA 94550 UNIVERSITY OF WASHINGTON ATTN: ATMOS. SCIENCES DEPT SEATTLE, WA 98195 PENN STATE UNIVERSITY ATTN: METEOROLOGY DEPT. 503 DEIKE BLDG. UNIVERSITY PARK, PA 16802

BUREAU OF METEOROLOGY ATTN: FLIGHT FORECASTER BOX 1289K, GPO MELBOURNE, VIC, 3001 AUSTRALIA METEOROLOGY OFFICE ATTN: FLIGHT FORECASTER BRACKNELL, BERKSHIRE RG 12 1SZ, ENGLAND

REPORT DOCUMENTATION PAGE

Form Approved OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of

this collection of information, including suggi Davis Highway, Suite 1204, Arlington, VA 22	estions for reducing this burden, to Washi 202-4302, and to the Office of Manager	ington Headquarters Services, Directors ment and Budget, Paperwork Reduction	ne for information Op on Project (0704-018	erations and Heports, 1215 Jefferson 8), Washington, DC 20503.		
1. Agency Use Only (Leave blank)	2. Report Date. March 1991	3. Report Type and i	Dates Covered.			
4. Title and Subtitle.			5. Funding I	Numbers.		
ExperCAT: An Expert :	Program Eleme	nt Na 62435N				
Prediction of Clear A	Project No.	RM35G80				
6. Author(s).			Task No.	3		
J.E. Peak				20055774		
			Accession No.	DN656766		
7. Performing Organization Name		•	8. Performin Report No	g Organization		
Computer Sciences Co	rporation, Monterey,	CA 93943-5006	neport NC	mnos.		
Naval Oceanographic a Atmospheric Directora Monterey, CA 93943-56	NOARL TO	NOARL Technical Note 101				
9. Sponsoring/Monitoring Agency	Name(s) and Address(es).			ng/Monitoring Agency		
Naval Ocean Systems (Center		Report N	umber.		
Code 54			NOARL TO	echnical Note 101		
San Diego, CA 92152-	5000		}			
11. Supplementary Notes.						
12a. Distribution/Availability State	ement.		12b. Distribu	ution Code.		
Annuauad fan nublia	losoo, distuibuti	on to colimitad	ĺ			
Approved for public i	release; distribution	on is uniimitea.	}			
13. Abstract (Maximum 200 word	s).					
· ·	n approach to the an	alysis and short-t	erm predi	ction of clear		
air turbulence (CAT)	is presented. CAT	is defined here as	nonconve	ctive turbulence		
occurring above 18,00						
and has extensive held is to guide a human o						
with CAT. ExperCAT						
confidence factor.	The user can optiona	illy view the selec	tions ent			
at the forecast. Thi	ree step-by-step exa	imple runs are prov	rided.			
1						
1						
1						
1						
						
14. Subject Terms. Turbulence	Artificial int	elligence	15.	Number of Pages. 34		
Clear air turbulence Satellite imagery	CAT Expert systems	_	16.	Price Code.		
17. Security Classification	18. Security Classification	19. Security Classificati	on 20.	Limitation of Abstract.		
of Report. UNCLASSIFIED	of This Page. UNCLASSIFIED	of Abstract. UNCLASSIFIED	, ,	Same as report		
NSN 7540-01-280-5500	UNCEASSITIED	29	<u>L</u>	Standard Form 258 (Fev. 2-83)		